

AUTOMATIC VOLTAGE REGULATOR

AVR PRO 25000 (25000VA) 3% 3F

The **AVR PRO 25000 VA3% 3F** automatic voltage regulator combines the features of 2 devices: a voltage regulator and surge protection device.

The most important features:

- **Stabilizes the voltage supplied at the stabilizer input**
- **Automatically reduces too high mains voltage and raises too low mains voltage to the appropriate level**
- **Protects connected devices against damage. If the voltage increases and exceeds a safe value, the stabilizer will automatically disconnect the device from the network, protecting it against damage**
- Works with power generators
- It suppresses interference introduced into the electrical network by other devices
- **It works in three-phase mode**

What makes the **AVR PRO 3F** special among other automatic voltage regulators?

PRO version with an innovative device. A **special service build-in mechanism allows to use of a very small tolerance of voltage - 3%.** It means that the output voltage will be very close to the target value, with the deflection of only 3%. This is very important concerning the sensitive electronic devices.

Main technical data:

MODEL	AVR PRO 25000VA 3% 3F
Power	25000VA
In voltage range	225-450VAC
Input voltage range for 1 phase	130V - 260V
Minimum starting voltage	225V±5V
Out voltage range	400V
Phases	1 phase / 3 phase
AVR stabilization precision	3%
Start delay switch	6s
Frequency	50Hz
Protection	High/low voltage protection, overload protection, high temperature protection, cicruit protection
Dimensions/Weight	545x230x430mm/38kg
Gross dimensions/Gross weight	640x360x600mm/50kg
Multipack dimensions/Multipack weight	640x360x600mm/50kg

AVR PRO 25000VA 3%3F:
INDEKS: 5AVX3F0250
EAN: 5904100451449



AVR PRO 25000VA 3% 3F



AVR PRO 25000VA 3% 3F



AVR PRO 25000VA 3% 3F