

CIRCULATING PUMP VOLT POLSKA OPTI ECO 25-60/130 (5-45W)

INDEKS: 3ZPSP256C3

EAN: 5903293765845

The energy-saving, electronic circulating pump **OPTI ECO 25-60/130 (5-45W)** is designed to force circulation in heating installations. It can be used in single and two-pipe installations and also when installing underfloor heating. The pump is equipped with a system that automatically adapts the pump characteristics to the installation in which it works. Thanks to the permanent magnets the pump can adapt its operation to the current demand, thus reducing energy losses.

The most important features:

- Simple installation and operation (external plug for connecting the pump)
- Universal design suitable for all home installations
- Low noise level
- Low energy efficiency ratio EEI <0.20
- High quality of production

What systems is the OPTI ECO pump best suited for?

- Constant temperature heating system with variable flow
- Heating system with variable pipeline temperature
- Heating system with night mode
- Air conditioning system
- Home central heating system CO

Main technical data:

MODEL	OPTI ECO 25-40/180 (5-22W)
Energy class	A 5-22W
Input voltage	230 V, -10%÷+6%, 50Hz
Relative humidity	95%
Sound pressure level	Lower than 43 dB
Ambient temperature	0°C ÷ +40°C
Liquid temperature	+ 2°C ÷ +100°C
Max. Working pressure	10bar
Protection	IP42
Dimensions	180x96x158mm
Weight	2,04kg
Gross dimensions/Weight	22x13x19,5cm/2,7kg
Mutipack dimensions/Weight	46x40,5x28cm/22,34kg



OPTI ECO 25-60/130 (5-45W)



OPTI ECO 25-60/130 (5-45W)



OPTI ECO 25-60/130 (5-45W)