

CIRCULATING PUMP VOLT POLSKA OPTI ECO S 25-60/180 (5-45W)

INDEKS: 3ZPSPB256B
EAN: 5903293765852

The energy-saving, electronic circulating pump **OPTI ECO S 25-60/180 (5-45W)** is designed to force circulation in heating installations. It can be used in single and two-pipe installations and also when installing underfloor heating. The pump is equipped with a system that automatically adapts the pump characteristics to the installation in which it works.

Thanks to the permanent magnets the pump can adapt its operation to the current demand, thus reducing energy losses.

The control panel has been launched on the top of the engine which makes it easier for the user to operate. On its disk there is a current electricity consumption displayed.

The most important features:

- Adjustable 3-speed speed
- Quiet work
- Low energy consumption (5W-45W)
- Energy-saving night mode
- Self-venting of the pump
- The three-speed engine which allows to adjust the pump's efficiency and pressure parameters to the user's needs

What systems is the OPTI ECO pump best suited for?

- Constant temperature heating system with variable flow
- Heating system with variable pipeline temperature
- Heating system with night mode
- Air conditioning system
- Home central heating system CO

Main technical data:

MODEL	OPTI ECO S 25-60/180 (5-45W)
Energy class	A 5-45W
Input voltage	230 V, -10%÷+6%, 50Hz
Relative humidity	95%
Sound pressure level	Lower than 43 dB
Ambient temperature	0°C ÷ +40°C
Liquid temperature	+ 2°C ÷ +100°C
Max. Working pressure	10bar
Protection	IP42
Dimensions	180x128x130mm/2,8kg
Weight	2,8kg
Gross dimensions/Weight	22x13x19,5cm/2,69kg
Mutipack dimensions/Weight	41,5x28x31,3cm/22,14kg



OPTI ECO S 25-60/180 (5-45W)



OPTI ECO S 25-60/180 (5-45W)



OPTI ECO S 25-60/180 (5-45W)